VinCore





Pleasure in every touch, quiet, easy to maintain, water-resistant

Rigid vinyl flooring

Collection 2025

WHY VINCORE?

Established in 2020, VinCore Flooring has quickly become a trusted name in the flooring industry, offering high-quality solutions that combine affordability, style, and ease of installation. Our rigid vinyl flooring provides an exceptional price-to-quality ratio, ensuring that customers receive durable, long-lasting flooring without breaking the bank.

We pride ourselves on our diverse range of colours and designs, making it easy for homeowners and businesses alike to find the perfect flooring to suit their aesthetic needs and preferences. Whether you're renovating a single room or outfitting an entire building, our wide selection ensures there's a perfect match for any space.

All of our rigid vinyl flooring is manufactured in a state-of-the-art facility that uses renewable energy and recycled material from internal production, underscoring our commitment to sustainability and environmentally responsible practices. We believe that quality products shouldn't come at the expense of the planet, and our modern production processes reflect this ethic.



1


WHAT IS RIGID VINYL FLOORING?

VinCore rigid vinyl flooring uses the most advanced technology and features SPC (stone polymer composite) base made from stone and innovative polymers.

VinCore rigid vinyl flooring is 100% water-resistant and can be installed in wet areas such as kitchens and bathrooms. VinCore rigid vinyl flooring is quiet thanks to integrated underlay that improves sound absorption.

Moreover, it offers warm underfoot and can be installed over underfloor heating system. Its sturdy construction reduces minor subfloor imperfections which makes installation easy and hassle-free.

VinCore is a combination of functionality and timeless design that features all characteristics of natural wood.



- 1. Pre-attached sound-absorbing IXPE underlay
- 2. Composite base with click system
- 3. High-resolution decorative film
- 4. Transparent wear layer
- 5. Anti-scratch polyurethane matt coating

WOOD

The WOOD collection exudes character and elegance, showcasing the beauty and uniqueness of various wood species.

Each decor is inspired by breathtaking landscapes and the rich heritage of Italy's most iconic regions, blending natural warmth with refined style.

Transform your space with the spirit of Italian artistry and the timeless charm of oak and hickory.







Plank format: 5 x 180 x 1220 mm.



Wear class 23/31 (heavy domestic use and moderate commercial use).



Floating installation (Uniclic click system).




HERRINGBONE

A stunning combination of elegance and sophistication.

The HERRINGBONE collection features four classic oak decors and one modern ash decor, all crafted in the iconic herringbone pattern to exude timeless style. Inspired by the picturesque landscapes and architecture of French regions and cities, these captivating colors bring a touch of French charm to any space.







Herringbone format 5 x 125 x 625 mm.



Wear class 23/31 (heavy domestic use and moderate commercial use).



Floating installation (Unidrop X click system).



WOOD+

WOOD+ is a collection where design meets quality.

Inspired by the captivating architecture of Italian cities, it highlights the natural beauty of oak and ash, embodying the essence of Mediterranean living. Earthy tones and rich textures seamlessly blend into any interior style – from classic to modern. With enhanced board thickness and a reinforced wear layer, this collection is perfect for residential homes as well as high-traffic commercial spaces.







Plank format: 6 x 180 x 1220 mm.



Wear class 23/33 (heavy domestic use and heavy commercial use).



Floating installation (Uniclic click system).



HERRINGBONE+

The HERRINGBONE+ collection perfectly captures the essence of French elegance, combining timeless style with exceptional craftsmanship.

Each decor highlights the natural beauty of carefully selected wood species, brought to life in the classic herringbone format.

Designed for both style and durability, this collection features a rigid construction and a thicker wear layer, making it an ideal choice for luxurious residential interiors as well as larger commercial spaces.







Herringbone format 6 x 125 x 625 mm.



Wear class 23/33 (heavy domestic use and heavy commercial use).



Floating installation (Unidrop X click system).



TECHNICAL SPECIFICATION

Floor type			multi-layer rigid vinyl flooring with click system				
Collection			WOOD	HERRINGBONE	WOOD+	HERRINGBONE+	
Format			plank	herringbone	plank	herringbone	
Overall thickness	*	ISO 24337	5 mm	5 mm	6 mm	6 mm	
Wear layer	×	EN 429	0,30 mm		0,55 mm		
Plank/tile size	\bigoplus	ISO 24337	180 x 1220 mm	125 x 625 mm	180 x 1220 mm	125 x 625 mm	
Total weight		ISO 23997	8400 g/m2	8200 g/m2	9500 g/m2	9200 g/m2	
Construction			composite base made from stone and polymers				
Surface			regular wood	light wood	regular wood	light wood	
			embossed	embossed	embossed	embossed	
inish			polyurethane matt coating				
Underlay			pre-attached IXPE				
Installation			floating (click system under license from Unilin)				
Warranty			20 years residential 25		25 years	residential	
			10 years commercial		10 years commercial		
Pieces per box			10	12	10	16	
Area per box			2,20 m2	0,94 m2	2,20 m2	1,25 m2	
Weight per box			18,5 kg	7,75 kg	21 kg	11,5 kg	
Fire resistance	B _{rr} -s1	EN 13501-1	Bfl-s1				
ormaldehyde emission	E1	EN 14041	E1				
Slip resistance	**************************************	EN 13893		D	S		
		DIN 51130:2014		R	10		
Dimension stability	K N	EN 23999	$\leq 0.15\%$ (norm: $\leq 0.25\%$)				
Curling	K N	EN 23999	pass (≦ 2 mm)				
Wear group		EN ISO 10874	23: domestic heavy 23: domestic heavy				
			31: commercial moderate		33: commercial heavy		
Abrasion resistance		EN13329 Annex E	pass (≧ 1	600 cycles)	pass (≧ 4	000 cycles)	
Castor chair	্ল	EN 425	pass (no visible change)				
Residual indentation		EN 434	pass (≦ 0,1 mm)				
Stain resistance		EN 438	pass (grade 5)				
UV resistance	7	ISO 105-B02	pass (≧ 6)				
Thermal conductivity		EN 12667	0,096 W/mK (floor + underlay)		1,09 W/mK (floor + underlay)		
Thermal resistance		EN 12667	0,052 (m2K)/W (floor + underlay) 0,055 (m2K)/W (floor + underlay)				
Underfloor heating			suitable for underfloor heating under certain conditions				
Acoustic insulation		EN ISO 717-2	ΔLw 19 dB				









For more details about warranty and installation, please visit our website or contact one of our sales representatives.

All images presented in this catalogue are not representative due to differences in printing. Please visit the nearest point of sale to see the real sample.

Alterations to product composition and materials used can be made to improve the quality.

EPUFLOORING Sp. z o.o.

Office: Kopcinskiego 77, 90-033 Lodz, Poland Warehouse: Ossendowskiego 3B, 93-228 Lodz, Poland help@epuflooring.pl www.vincore.pl

